



V2000



2 °C - 130 °C
Max. 10 bar
 $\Delta p_{max} = 1.0 \text{ bar}$

A

B

C

$\alpha = 90^\circ$

$\alpha = 0^\circ$

DN10: 40 Nm
DN15: 60 Nm
DN20: 80 Nm

D

n → Tab / App

homecomfort.resideo.com/TRV

Tab: Q_{nom} kg/h [10kPa/0.1bar, 2K p-band]

n	1	2	3	4	5	6
FX	10	17	27	43	59	70
SX	20	30	50	90	135	170
LX	20	50	100	150	200	225

BB: 140 l/h, UB: 190 l/h

VA8200A001 	VA8201TRV01 	VA8201PI04 	FX: VS1200FX01 SX: VS1200SX01 LX: VS1200LX01 BB: VS1200BB01 UB: VS1200UB01
----------------	-----------------	----------------	--

For more information
homecomfort.resideo.com/europe



Ademco 1 GmbH
Hardhofweg 40
74821 MOSBACH
GERMANY
Phone: +49 6261 810
Fax: +49 6261 81309

Manufactured for and on behalf of the
Pittway Sàrl, La Pièce 4, 1180 Rolle, Switzerland
by its Authorised Representative Ademco 1 GmbH
MU2H-2112GE23 R0720
Subject to change
© 2020 Pittway Sàrl. All rights reserved.
This document contains proprietary information of
Pittway Sàrl and its affiliated companies and is
protected by copyright and other international
laws. Reproduction or improper use without specific
written authorisation of Pittway Sàrl is strictly
forbidden. The Honeywell Home trademark is used
under license from Honeywell International Inc.