

Camina & Schmid Lina W TV 7345 h/s, front version: Kristall, surrounding: customised design



Fireplace inserts with hydronic technology

i

Tunnel version and hydronic technology

The Lina W TV 73..s/h fireplace insert intelligently combines these properties in a fireplace insert.

Flue gas connector

The flue gas connector can be equipped with a horizontal flue gas connector (optional). Available in the following sizes: Ø 180 mm (Lina W TV 73..s/h) and Ø 200 mm (Lina W 67..s/h, Lina W 73..s/h)

Integrated SMR fire chamber sensor bracket

No further accessories needed.

Firebox inner lining

Smooth chamotte in "Premium White" (optionally in anthracite or cast iron at a surcharge).

Grate-free combustion (Lina W TV 73..s/h)

11 kW (DE) and 20 kW (Export) outputs have been checked with a water output of 60 %.

Detachable heat exchanger (Lina W TV 73..s/h)

Simplifies transport and assembly

Body sides

Double-walled to pre-warm secondary air for efficient and clean combustion.

Door fronts

Front hinged / rear side hinged

You can opt for a door hinged on left or right.

Front guillotine / rear side hinged



Alternatively opt for a guillotine front.


Double glass


Double glass ensures approx. 30% less heat distribution through the ceramic glass and higher combustion chamber temperatures. Specially coated panes of glass provide for more efficient water output.




Lina W TV 7345 s/s · 7351 s/s

Art. no.	Art. no.	H, cm	Price / €	Product details
Standard  Door hinge on left	Door hinge on right 			<ul style="list-style-type: none"> - Nominal heat output: 11kW (DE) - Nominal heat output: 20 kW (Export) - Fireplace insert: Tunnel version - Front width: 730 mm - Heat distribution: water-side 60%, air-side 40% - Max. operating pressure: 3 bar - Water content: 37.5 l - Integrated SMR fire chamber sensor bracket - Including thermal discharge safety device (TAS) - Door: hinged (front and rear side), self-closing - Double glass - Low fireplace substructure: 170 mm - Cast-iron flue gas connector: Ø180 mm, Optional: horizontal flue gas connector (see page 55) - Optional: Combustion air connector: Ø150 mm (left, right) available at a surcharge (see page 53) - Optional: Combustion air connector: Ø150 mm (bottom) available at a surcharge - Without cast grate / ash box
Kristall 64/1400-3913	64/1400-3923	45	5,750.00	
Kristall 64/1410-3913	64/1410-3923	51	5,750.00	








Data sheet
Lina W TV 73.. s/s




Lina W TV 7345 h/s · 7351 h/s

Art. no.	Art. no.	H, cm	Price / €	Product details
Standard  Door: guillotine				<ul style="list-style-type: none"> - Nominal heat output: 11kW (DE) - Nominal heat output: 20 kW (Export) - Fireplace insert: Tunnel version - Front width: 730 mm - Heat distribution: water-side 60%, air-side 40% - Max. operating pressure: 3 bar - Water content: 37.5l - Integrated SMR fire chamber sensor bracket - Including thermal discharge safety device (TAS) - Door: guillotine (tilts for cleaning), not supplied self-closing from the factory (weights for conversion supplied), rear side: hinged - Double glass - Low fireplace substructure: 170 mm - Cast-iron flue gas connector: Ø180 mm, optional: horizontal flue gas connector (see page 55) - Optional: Combustion air connector: Ø150 mm (left, right) available at a surcharge (see page 53) - Optional: Combustion air connector: Ø150 mm (bottom) available at a surcharge - Without cast grate / ash box
Kristall 64/1450-3933		45	6,450.00	
Kristall 64/1460-3933		51	6,450.00	







Data sheet
Lina W TV 73.. h/s



Options	Dimensions	Art. no.	Details	Surcharge / €
NEW Fire box inner lining, cast iron, for Lina W TV 51 cm height				220.00
Fire box inner lining, anthracite chamotte				120.00
Combustion air connector bottom, factory pre-assembled	Ø 150 mm	21/5120-0021	see page 53	55.00

Sales prices in € plus VAT | Subject to errors and omissions. Illustrations are similar.

Lina W 6751 s 

Art. no.	Art. no.	H, cm	Price / €	Product details
Standard  Door hinge on left	Door hinge on right 			<ul style="list-style-type: none"> - Nominal heat output: 14.5 kW - Front: open - Front width: 670 mm - Heat distribution: water-side 70%, air-side 30% - Max. operating pressure: 3 bar - Water content: 68 l - Insert: fully water-washed - Including thermal discharge safety device (TAS) - Door: hinged, self-closing - Double glass - Low fireplace substructure: 170 mm - Flue gas connector: Ø 200 mm - Combustion air connector: Ø 150 mm (left, right, rear) - Optional: Combustion air connector: Ø 150 mm (bottom) available at a surcharge
Kristall 64/1310-3010	64/1310-3020	51	5,100.00	
Insert prepared for "Stone" external fuel-door 64/1310-3510	64/1310-3520	51	5,100.00	






Fig. Lina W 6751 s



Data sheet
Lina W 6751 s

A+

Lina W 6751 h 

Art. no.	Art. no.	H, cm	Price / €	Product details
Standard  Door: guillotine				<ul style="list-style-type: none"> - Nominal heat output: 14.5 kW - Front: open - Front width: 670 mm - Heat distribution: water-side 70%, air-side 30% - Max. operating pressure: 3 bar - Water content: 68 l - Insert: fully water-washed - Including thermal discharge safety device (TAS) - Door: guillotine (tilts for cleaning), not supplied self-closing from the factory (weights for conversion supplied) - Double glass - Low fireplace substructure: 170 mm - Flue gas connector: Ø 200 mm - Combustion air connector: Ø 150 mm (left, right, rear) - Optional: Combustion air connector: Ø 150 mm (bottom) available at a surcharge
Kristall 64/1360-3030		58	5,800.00	
Insert prepared for "Stone" external fuel-door 64/1360-3530		58	5,800.00	





Fig. Lina W 6751 h







Data sheet
Lina W 6751 h

A+

Options / Accessories	Dimensions	Art. no.	Details	Surcharge / €
NEW Fire box inner lining, cast iron, for Lina W 51 cm height				330.00
Fire box inner lining, anthracite chamotte				120.00
Combustion air connector bottom, factory pre-assembled	Ø 150 mm	21/5120-0021	see page 53	55.00
External fuel-door "Stone", self-closing door		66/5776-1570	see page 53	1,000.00

Sales prices in € plus VAT | Subject to errors and omissions. Illustrations are similar.

Lina W 7363 s

Art. no.	Art. no.	H, cm	Price / €	Product details
Standard  Door hinge on left	Door hinge on right 			<ul style="list-style-type: none"> - Nominal heat output: 14.9 kW - Front: open - Front width: 730 mm - Heat distribution: water-side 70%, air-side 30% - Max. operating pressure: 3 bar - Water content: 80 l - Insert: fully water-washed - Including thermal discharge safety device (TAS) - Door: hinged, self-closing - Double glass - Low fireplace substructure: 170 mm - Flue gas connector: Ø200 mm - Combustion air connector: Ø150 mm (left, right, rear) - Optional: Combustion air connector: Ø150 mm (bottom) available at a surcharge
Kristall 64/1430-3010	64/1430-3020		5,250.00	
Insert prepared for "Stone" external fuel-door 64/1430-3510	64/1430-3520		5,250.00	









Fig. Lina W 7363 s



Data sheet
Lina W 7363 s



Lina W 7363 h

Art. no.	Art. no.	H, cm	Price / €	Product details
Standard  Door: guillotine				<ul style="list-style-type: none"> - Nominal heat output: 14.9 kW - Front: open - Front width: 730 mm - Heat distribution: water-side 70%, air-side 30% - Max. operating pressure: 3 bar - Water content: 80 l - Insert: fully water-washed - Including thermal discharge safety device (TAS) - Door: guillotine (tilts for cleaning), not supplied self-closing from the factory (weights for conversion supplied) - Double glass - Low fireplace substructure: 170 mm - Flue gas connector: Ø200 mm - Combustion air connector: Ø150 mm (left, right, rear) - Optional: Combustion air connector: Ø150 mm (bottom) available at a surcharge
Kristall 64/1480-3030			5,950.00	
Insert prepared for "Stone" external fuel-door 64/1480-3530			5,950.00	






Fig. Lina W 7363 h



Data sheet
Lina W 7363 h



Options / Accessories	Dimensions	Art. no.	Details	Surcharge / €
Fire box inner lining, anthracite chamotte				120.00
Combustion air connector bottom, factory pre-assembled	Ø 150 mm	21/5120-0021	see page 53	55.00
External fuel-door "Stone", self-closing door		66/5776-1570	see page 53	1,000.00

Sales prices in € plus VAT | Subject to errors and omissions. Illustrations are similar.

Ekko W L 67(45)51 s (with frame doors) 






	Art. no.	H, cm	Price / €	Product details
Standard				
				Door hinge on right 
Kristall	64/2610-3020		5,700.00	<ul style="list-style-type: none"> - Nominal heat output: 14.9 kW - Front: Open on 2 side - Front width: 670 mm - Side part depth: 450 mm - Heat distribution: water-side 50%, air-side 50% - Max. operating pressure: 3 bar - Water content: 52 l - Insert: fully water-washed - Including thermal discharge safety device (TAS) - Door 2-section - With frame doors - Door: hinged, self-closing - Double glass - Flue gas connector: Ø 200 mm - Combustion air connector: Ø 125 mm (right, rear, bottom) - Optional: Combustion air connector: Ø 150 mm (bottom) available at a surcharge
Insert prepared for "Stone" external fuel-door	64/2610-3520		5,700.00	
 Data sheet Ekko W L 67(45)51 s (with frame doors)				



Fig. Ekko W L 67(45)51 s
(with frame doors)

Ekko W R 67(45)51 s (with frame) 






	Art. no.	H, cm	Price / €	Product details
Standard				
				Door hinge on left 
Kristall	64/2710-3010		5,700.00	<ul style="list-style-type: none"> - Nominal heat output: 14.9 kW - Front: Open on 2 side - Front width: 670 mm - Side part depth: 450 mm - Heat distribution: water-side 50%, air-side 50% - Max. operating pressure: 3 bar - Water content: 52 l - Insert: fully water-washed - Including thermal discharge safety device (TAS) - Door 2-section - With frame doors - Door: hinged, self-closing - Double glass - Flue gas connector: Ø 200 mm - Combustion air connector: Ø 125 mm (left, rear, bottom) - Optional: Combustion air connector: Ø 150 mm (bottom) available at a surcharge
Insert prepared for "Stone" external fuel-door	64/2710-3510		5,700.00	
 Data sheet Ekko W R 67(45)51 s (with frame doors)				



Fig. Ekko W R 67(45)51 s
(with frame doors)

Options / Accessories	Dimensions	Art. no.	Details	Surcharge / €
NEW Fire box inner lining, cast iron, for Ekko W 51 cm height				280.00
Fire box inner lining, anthracite chamotte				120.00
Combustion air connector bottom, factory pre-assembled	Ø 150 mm	21/5120-0021	see page 53	55.00
External fuel-door "Stone", self-closing door		66/5776-1570	see page 53	1,000.00

Sales prices in € plus VAT | Subject to errors and omissions. Illustrations are similar.

Ekko W L 67(45)51 s (frameless)

	Art. no.	H, cm	Price / €	Product details
Standard				<ul style="list-style-type: none"> - Nominal heat output: 14.9 kW - Front: Open on 2 side - Front width: 670 mm - Side part depth: 450 mm - Heat distribution: water-side 50%, air-side 50% - Max. operating pressure: 3 bar - Water content: 52 l - Insert: fully water-washed - Including thermal discharge safety device (TAS)
				<ul style="list-style-type: none"> - One-piece frame - Door: hinged, self-closing - Glass: 1-section - Flue gas connector: Ø200 mm - Combustion air connector: Ø125 mm (right, rear, bottom) - Optional: Combustion air connector: Ø150 mm (bottom) available at a surcharge (see page 53)
Kristall	64/2610-7320	51	5,700.00	
Insert prepared for "Stone" external fuel-door	64/2615-7320	51	5,700.00	



Fig. Ekko W L 67(45)51 s (one-piece frame)



Data sheet
Ekko W L 67(45)51 s
(one-piece frame)



Ekko W R 67(45)51 s (frameless)

	Art. no.	H, cm	Price / €	Product details
Standard				<ul style="list-style-type: none"> - Nominal heat output: 14.9 kW - Front: Open on 2 side - Front width: 670 mm - Side part depth: 450 mm - Heat distribution: water-side 50%, air-side 50% - Max. operating pressure: 3 bar - Water content: 52 l - Insert: fully water-washed - Including thermal discharge safety device (TAS)
				<ul style="list-style-type: none"> - One-piece frame - Door: hinged, self-closing - Glass: 1-section - Flue gas connector: Ø200 mm - Combustion air connector: Ø125 mm (left, rear, bottom) - Optional: Combustion air connector: Ø150 mm (bottom) available at a surcharge (see page 53)
Kristall	64/2710-7310	51	5,700.00	
Insert prepared for "Stone" external fuel-door	64/2715-7310	51	5,700.00	



Fig. Ekko W R 67(45)51 s (one-piece frame)



Data sheet
Ekko W R 67(45)51 s
(one-piece frame)






Options / Accessories	Dimensions	Art. no.	Details	Surcharge / €
NEW Fire box inner lining, cast iron, for Ekko W 51 cm height				280.00
Fire box inner lining, anthracite chamotte				120.00
Combustion air connector bottom, factory pre-assembled	Ø 150 mm	21/5120-0021	see page 53	55.00
External fuel-door "Stone", self-closing door		66/5776-1570	see page 53	1,000.00

Sales prices in € plus VAT | Subject to errors and omissions. Illustrations are similar.






Energy efficiency class
in accordance with (EU) 2015/1186

Ekko W L 67(45)51 h 

	Art. no.	H, cm	Price / €	Product details	
Standard	Door: guillotine 				
Kristall Insert prepared for "Stone" external fuel-door	 <i>Fig. Ekko W L 67(45)51 h</i>	64/2660-3030	51	6,400.00	<ul style="list-style-type: none"> - Nominal heat output: 14.9 kW - Front: Open on 2 side - Front width: 670 mm - Side part depth: 450 mm - Heat distribution: water-side 50% (with DVGL: -60%) - Heat distribution: air-side 50% (with DVGL: -40%) - Max. operating pressure: 3 bar - Water content: 52 l - Insert: fully water-washed - Including thermal discharge safety device (TAS) - Door: guillotine (hinged for cleaning), not supplied self-closing from the factory (weights for conversion supplied) - Glass: 1-section - Flue gas connector: Ø200 mm - Combustion air connector: Ø125 mm (left, rear, bottom) - Optional: Combustion air connector: Ø150 mm (bottom) available at a surcharge (see page 53)
		64/2665-3030	51	6,400.00	
 Data sheet Ekko W L 67(45)51 h				A⁺	

Ekko W R 67(45)51 h 

	Art. no.	H, cm	Price / €	Product details	
Standard	 Door: guillotine				
Kristall Insert prepared for "Stone" external fuel-door	 <i>Fig. Ekko W R 67(45)51 h</i>	64/2760-3030	51	6,400.00	<ul style="list-style-type: none"> - Nominal heat output: 14.9 kW - Front: Open on 2 side - Front width: 670 mm - Side part depth: 450 mm - Heat distribution: water-side 50% (with DVGL: -60%) - Heat distribution: air-side 50% (with DVGL: -40%) - Max. operating pressure: 3 bar - Water content: 52 l - Insert: fully water-washed - Including thermal discharge safety device (TAS) - Door: guillotine (hinged for cleaning), not supplied self-closing from the factory (weights for conversion supplied) - Glass: 1-section - Flue gas connector: Ø200 mm - Combustion air connector: Ø125 mm (left, rear, bottom) - Optional: Combustion air connector: Ø150 mm (bottom) available at a surcharge (see page 53)
		64/2765-3030	51	6,400.00	
 Data sheet Ekko W R 67(45)51 h				A⁺	

Options / Accessories	Dimensions	Art. no.	Details	Surcharge / €
 Double glass				500.00
NEW Fire box inner lining, cast iron, for Ekko W 51 cm height				280.00
Fire box inner lining, anthracite chamotte				120.00
Combustion air connector, factory pre-assembled	Ø 150 mm	21/5120-0021	see page 53	55.00
External fuel-door "Stone", self-closing door		66/5776-1570	see page 53	1,000.00

Sales prices in € plus VAT | Subject to errors and omissions. Illustrations are similar.